

Features

- Full blocking capability over wide temperature range
- Hermetic sealed ceramic package

Key Parameters


V_{RRM}	= 1800V
$I_{F(AV)}$	= 460A
I_{FSM}	= 6kA
$V_{F(TO)}$	= 0.70V
r_F	= 0.66mΩ

Applications


- Uncontrolled Rectifiers
- Battery Chargers
- Power Supplies

Symbol	Characteristic	Conditions	T _J [°C]	Value	Unit
BLOCKING					
V_{RRM}	Repetitive peak reverse voltage		170	200 - 1800	V
I_{RRM}	Repetitive peak reverse current	$V = V_{RRM}$	170	20	mA
CONDUCTING					
$I_{F(AV)}$	Mean Forward current	180° sin ,50 Hz, T _c =95°C, Double side cooled		460	A
I_{FRMS}	RMS Forward current			722	A
I_{FSM}	Surge Forward current	Sine wave, 10 ms Without reverse voltage	25	6000	A
			170	5000	A
$I^2 t$	$I^2 t$	Sine wave, 10 ms Without reverse voltage	25	180 x 10 ³	A ² s
			170	125 x 10 ³	A ² s
V_F	Peak Forward voltage	Peak forward current = 1500A	170	1.69	V
$V_{F(TO)}$	Threshold voltage		170	0.70	V
r_F	Forward slope resistance		170	0.66	mΩ
MOUNTING					
$R_{th(j-c)}$	Thermal impedance, sin 180°	Junction to case, Double side cooled		0.112	°C/W
$R_{th(c-h)}$	Thermal impedance	Case to heatsink, Double side cooled		0.015	°C/W
T_j	Max. junction temperature			170	°C
T_{stg}	Storage temperature			-40 170	°C
M	Mounting Torque			5 - 6	kN
W	Weight (Approx.)			70	gm


DISSIPATION CHARACTERISTICS
SINE WAVE




FORWARD CURRENT DERATING CURVE
SINE WAVE



DISSIPATION CHARACTERISTICS
SQUARE WAVE




FORWARD CURRENT DERATING CURVE
SQUARE WAVE





FORWARD CHARACTERISTICS

$T_j = 170^\circ\text{C}$



SURGE CHARACTERISTICS





ORDERING INFORMATION

GDZP	460	C	X X
Rectifier Diode	Current code	Capsule Package	Voltage Code Code X 100 = V _{RRM}

Order Code GDZP460C18 – 1800V V_{RRM1}, Capsule diode

Outline

